

Smart Hybrid Light 4MP outdoor IP dome



- HYUNDAI IP Dome
- 4MP@20ips, H.265+/H.265
- ICR, 0.01 lux, Smart Hybrid Light 20m
- 2.8mm fixed optics
- Digital WDR
- People detection
- RJ45, Onvif, IP67, 3AXIS
- 12V DC / PoE



Reference / Model	HYU-1095 / HYU-1095
4 megapixel 1/2.8" CMOS sensor	
Compression formats: H.265+, H.264+, H.265, H.264, MJPEG	
Digital resolution: 4MP (2560x1440), 1080P (1920x1080), 720P (1280x720), VGA (640x480), Q720P (640x360)	
Stream 1: 4MP (20 fps), 1080P, 720P (25/24 fps)	
Stream 2: 720P, VGA, Q720P (25/24 fps)	
Day/night mode with removable mechanical filter	
Dual intelligent illumination by IR and white light, up to 20 meters	
0.01 lux F2.2 (color), 0 lux IR On	
2.8 mm fixed optics	
Angle of view: 104°(H), 57°(V), 123°(D)	
Imaging modes: BLC, HLC, digital WDR, 3D-DNR	
Saturation, brightness, contrast, sharpness, gain and white balance adjustments from client software or web browser	
Supports 1 fixed ROI for main stream	
1 programmable privacy mask	

Smart Hybrid Light 4MP outdoor IP dome

Reference / Model	HYU-1095 / HYU-1095
	Motion video sensor with person detection
	Built-in microphone
	Auto-adaptive RJ45 10/100M Ethernet interface
	Network protocols: TCP/IP, ICMP, DHCP, DNS, HTTP, RTP, RTCP, RTSP, NTP, IGMP, IPv4, IPv6, UDP, QoS, SNMP, DDNS
	ONVIF (S/T), ISAPI, SDK support
	Up to 32 users and 6 simultaneous views
	Compatible with web browsers
	Power supply: 12V DC (±25%) / PoE (802.3af)
	Power consumption: 5W (12V) / 6.5W (PoE)
	Storage temperature -30°C ~ +45°C
	Storage humidity: ≤95% (non-condensing)
	Operating temperature from -30°C ~ +45°C
	Operating humidity: ≤95% (non-condensing)
	IP67 degree of protection
	Plastic housing
	Dimensions: Ø110 x 89.2 mm
	Net weight: 345 g
	Gross weight: 588 g
	3AXIS: 0°~360°(PAN), 0°~75°(TILT), 0°~360°(ROTATION)