

Item code: 70415-HXVR-08E102H1

Product description: DVR EASY Series

Main features: TURBO HD DVR 8 Channels: Support H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 video compression. HDTV input: 4 MP, AHD input: 4 MP, HDCVI input: 2 MP, CVBS input: PAL/NTSC, Audio IN/Out: 1/1, Serial interface: RS-485 (half-duplex), USB interface: 2 $\tilde{\Lambda}$ USB 2.0, Power supply: 12 Vdc.


SPECIFICATIONS

Recording	
Video compression	H.265 Pro+/H.265 Pro/H.265/H.264+/H.264
Encoding resolution	<u>When 1080 p Lite mode is not enabled:</u> 4 MP lite/3 MP/1080 p/720 p/VGA/WD1/4CIF/CIF <u>When 1080 p Lite mode is enabled:</u> 4 MP lite/3 MP/1080 p lite/720 p lite/VGA/WD1/4CIF/CIF
Frame rate	Main stream: <u>When 1080 p Lite mode is not enabled:</u> For 4 MP stream access: 4 MP lite@15 fps; 1080 p lite/720 p/WD1/4CIF/VGA/CIF@25 fps (P)/30 fps (N) For 3 MP stream access: 3 MP/1080 p/720 p/VGA/WD1/4CIF/CIF@15 fps For 1080 p stream access: 1080 p/720 p@15 fps; VGA/WD1/4CIF/CIF@25 fps (P)/30 fps (N) For 720 p stream access: 720 p/VGA/WD1/4CIF/CIF@25 fps (P)/30 fps (N) <u>When 1080 p Lite mode enabled:</u> 4 MP lite/3 MP@15 fps; 1080 p lite/720 p lite/VGA/WD1/4CIF/CIF@25 fps (P)/30 fps (N) Sub-stream: WD1/4CIF/CIF@25 fps (P)/30 fps (N)
Video bit rate	32 Kbps to 10 Mbps
Dual stream	Support
Stream type	Video, Video & Audio
Audio compression	G.711u
Audio bit rate	64 Kbps
Video and Audio	
IP video input	4-ch (up to 12-ch) Up to 6 MP resolution Support H.265+/H.265/H.264+/H.264 IP cameras
Analog video input	8-ch BNC interface (1.0 Vp-p, 75 Ω), supporting coaxitron connection
HDTV input	4 MP, 3 MP, 1080 p 25, 1080 p 30, 720 p 25, 720 p 30, 720 p 50, 720 p 60


BS OHSAS 18001:2007
 Occupational Health and
 Safety Management System

ISO 9001:2015
 Quality Management
 System

ISO 14001:2015
 Environmental Management
 System

CI ITPI: 2015
 100% Made in Italy
 Certificate


MAZi – Brand distributed by **LINCE ITALIA S.p.A.**
 Via Variante di Cancelliera s.n.c., 00072 Ariccia (RM) Italia
 Tel.: +39 06 92928252 - Fax: +39 06 92942586
www.lincede.net - info@lincede.net
MD-03.11 Rev. 6 - Pag.: 1 di 2

	<i>*: The 3 MP signal input is only available for channel 1 of DS-7104HQHI-K1, channel 1/2 of DS-7108HQHI-K1, and channel 1/2/3/4 of DS-7116HQHI-K1</i>
AHD input	4 MP, 1080 p 25, 1080 p 30, 720 p 25, 720 p 30
HDCVI input	4 MP, 1080 p 25, 1080 p 30, 720 p 25, 720 p 30
CVBS input	Support
VGA output	1-ch, 1920 × 1080/60 Hz, 1280 × 1024/60 Hz, 1280 × 720/60 Hz, 1024 × 768/60 Hz
HDMI output	1-ch, 1920 × 1080/60 Hz, 1280 × 1024/60 Hz, 1280 × 720/60 Hz, 1024 × 768/60 Hz
Audio input	1-ch, RCA (2.0 Vp-p, 1 KΩ)
Audio output	1-ch, RCA (Linear, 1 KΩ)
Two-way audio	1-ch, RCA (2.0 Vp-p, 1 KΩ) (using the first audio input)
Synchronous playback	8-ch
Network	
Remote connection	64
Network protocol	TCP/IP, PPPoE, DHCP, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP™, HTTPS, ONVIF
Network interface	1, RJ45 10M/100M/1000M self-adaptive Ethernet interface
Auxiliary Interface	
SATA	1 SATA interfaces
Capacity	Up to 6 TB capacity for each disk
USB interface	<i>Rear panel:</i> 2 × USB 2.0
Alarm in/out	N/A
General	
Power supply	12 Vdc, 1,33 A
Consumption (without HDD)	≤ 12 W
Working temperature	-10 °C ÷ 55 °C (14 °F ÷ 131 °F)
Working humidity	10% ÷ 90%
Dimension (W × D × H)	200 × 200 × 45 mm (7.9 × 7.9 × 1.8 inch)
Weight (without HDD)	≤ 1 kg (2.2 lb)



BS OHSAS 18001:2007
Occupational Health and Safety Management System



ISO 9001:2015
Quality Management System



ISO 14001:2015
Environmental Management System



CI ITPI: 2015
100% Made in Italy Certificate



MAZi – Brand distributed by **LINCE ITALIA S.p.A.**
Via Variante di Cancelliera s.n.c., 00072 Ariccia (RM) Italia
Tel.: +39 06 92928252 - Fax: +39 06 92942586

www.lince.net – info@lince.net

MD-03.11 Rev. 6 - Pag.: 2 di 2